

PFF19-1902

DESCRIPTION

FRONT ARM REAR BUSH

INSTALLATION GUIDE

Contents (parts per pack):

- 2 x Polyurethane A Bushes 1 x Grease
- 2 x Polyurethane B Bushes

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- -all work to be carried out by a licensed technician;
- -all safety precautions adhered to;
- -wheel alignment to be checked and adjusted as required after any suspension work.
- -All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

- 1. Remove the bracket from the arm and remove the original bush from the bracket.
- 2. Clean any dirt or corrosion off the bracket and file off any sharp edges.
- 3. With the chamfered edge of part B facing the rear of the car, push the bush into the bracket, as shown in Figure 1.
- 4. Apply some of the supplied grease into the bore of part B and on the shaft of part A.
- 5. Push part A into the bore of part B while it is in the bracket.
- 6. Refit the bracket back onto the arm and tension all hardware to manufacturers recommended torque settings.




Figure 2 - diagram showing part A and part B fitted into each other



Figure 1 - diagram showing how part A and part B fits inside the bracket and into each other