

PFF60-1422

DESCRIPTION

Lower Engine Mount

INSTALLATION GUIDE

Contents (parts per pack):

2 x Polyurethane A Bushes 1 x PTFE/Silicone Grease

1 x Aluminium mount with prefitted bush and sleeve

2 x Nylon Washers 1 x Stainless Steel Sleeve

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- -all work to be carried out by a licensed technician;
- -all safety precautions adhered to;
- -wheel alignment to be checked and adjusted as required after any suspension work.
- -All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

- 1. Press the 2 black Polyurethane bushes into either side of the smaller end of the black aluminium mount.
- 2. Apply the supplied grease to the outside of the stainless steel sleeve, and press it into the bush at the smaller end of the mount.
- 3. Apply the supplied grease to both faces of both bushes on the mount.
- Slip the nylon washers over either end of the 4. smaller sleeve.
- 5. Remove the Renault lower engine mount and bracket assmbely by unbolting the bracket from the gearbox, and removing the bolt from the subframe.
- 6. Unbolt the Renault mount from the bracket, and replace with PFF60-1422 by bolting the smaller end into the bracket.
- 7. Replace the new mount/bracket assembly on the car, and tension all hardware to manufacturers recommended torque settings.



