

PART NUMBER *

PFF27-401

DESCRIPTION

FRONT CONTROL ARM FRONT BUSH

INSTALLATION GUIDE

Contents (parts per pack):

2 x A Polyurethane Bushes 2 x B Polyurethane Bushes

2 X Stainless Steel Sleeve 1 x PTFE/Silicone Grease

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- -all work to be carried out by a licensed technician;
- -all safety precautions adhered to;
- -wheel alignment to be checked and adjusted as required after any suspension work.
- -All fasteners must be tensioned to manufacturer's torque settings.



Fitting Instructions:

- 1. Remove the original rubber bush including the outer shell from the wishbone.
- 2. Clean any dirt or corrosion from the bore of the arm, and file off any sharp edges with a rounded file to prevent damaging the polyurethane bush.
- 3. Push the thicker A Bush into the wishbone from the front of the wishbone as shown in Fig 1.
- 4. Push the thinner B Bush in from the rear of the wishbone as shown in Fig 1.
- 5. Apply some of the supplied grease to the bore of the bush and push in the stainless steel sleeve.
- 6. Refit the wishbone to the vehicle and tension all hardware to the manufacturer's recommended torque settings.

