

DESCRIPTION

PFR5-4610

REAR SUBFRAME FRONT BUSH

INSTALLATION GUIDE

Product description:

These bushes give a positive location of the rear sub frame, reducing movement at the rear end under cornering

Contents (parts per pack):

2 x bushes (2 x A Upper parts & 2 x B Lower parts)

2 x metal sleeves

1 x grease

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a quide and in conjunction with workshop manual. It is recommended that:

- all work to be carried out by a licensed technician;
- all safety precautions adhered to:
- wheel alignment to be checked and adjusted as required after any suspension work.

All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

- Remove original bush. Clean sub frame of any rust and dirt.
- Fit the upper part PFR5-4610A into the sub frame from the upper chassis side, 2. align the bush making sure the recessed area on the larger diameter fits over the welded section of the sub frame.
- Fit the lower part PFR5-4610B into the sub frame from the lower (road) side. Align 3. the shaped face to mesh neatly into the impression on the lower mounting plate.
- 4. Apply the supplied grease to the bore of the bush, the outside of the stainless steel sleeve and the upper and lower faces of the bush.
- Push the stainless steel sleeve into the bush. 5.
- Refit using the original bolt and washer, tightening to manufactures recommended torque settings.





