



PART NUMBER
PFR46-204G

DESCRIPTION
REAR UPPER ARM BUSH - CAMBER ADJUST

INSTALLATION GUIDE

PFR46-204G

REAR UPPER ARM BUSH-CAMBER ADJU
CAMBER adjustment range +/-1.5 deg

Contents (parts per pack):

- 16 x bushes
- 8 x centre metal sleeves
- 1 x adjusting spanner
- 1 x grease



Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- all work to be carried out by a licenced technician;
- all safety precautions are adhered to;
- wheel alignment to be checked and adjusted after any suspension work.

All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

1. Remove rear upper control/radius arm from the car.
2. Using a workshop press with suitable adaptors, carefully press out original bushes from control/radius arm and hub. Clean bore of any burrs or dirt.
3. Insert new Powerflex bushes into control/radius arm and hub.
4. Liberally lubricate the bore of the new bush with grease supplied and press new metal sleeve inside the bush.

Tip: If the required adjustment is known, it is generally best to pre-adjust to maximum positive camber setting prior to re-fitment.

5. Refit refurbished control/radius arm to car.
6. Tighen all hardware to manufacturer's original torque settings.
7. Test drive the vehicle, and perform full wheel alignment check and adjustment.

To adjust camber:

a) Loosen bush mounting bolts and using supplied spanner rotate the centre sleeve to the desired position.

b) Fine adjustment can then be performed using the original camber adjustment mechanism.



PART NUMBER
PFR46-204G

DESCRIPTION
REAR UPPER ARM BUSH - CAMBER ADJUST

INSTALLATION GUIDE

PFR46-204G

REAR UPPER ARM BUSH-CAMBER ADJU
CAMBER adjustment range +/-1.5 deg

Contents (parts per pack):

- 16 x bushes
- 8 x centre metal sleeves
- 1 x adjusting spanner
- 1 x grease



Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- all work to be carried out by a licenced technician;
- all safety precautions are adhered to;
- wheel alignment to be checked and adjusted after any suspension work.

All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

1. Remove rear upper control/radius arm from the car.
2. Using a workshop press with suitable adaptors, carefully press out original bushes from control/radius arm and hub. Clean bore of any burrs or dirt.
3. Insert new Powerflex bushes into control/radius arm and hub.
4. Liberally lubricate the bore of the new bush with grease supplied and press new metal sleeve inside the bush.

Tip: If the required adjustment is known, it is generally best to pre-adjust to maximum positive camber setting prior to re-fitment.

5. Refit refurbished control/radius arm to car.
6. Tighen all hardware to manufacturer's original torque settings.
7. Test drive the vehicle, and perform full wheel alignment check and adjustment.

To adjust camber:

a) Loosen bush mounting bolts and using supplied spanner rotate the centre sleeve to the desired position.

b) Fine adjustment can then be performed using the original camber adjustment mechanism.